



albin.pump
marine since 1928



Waste Water Diaphragm Pump 22L (5.8 GPM) 12V

Single chamber, self priming, diaphragm pump 12V for grey or bilge water. Shower drain, transfer or pump out. Capacity 22 L/min (5,8 GPM), flexible installation with 360 degree rotational ports. Quiet operation and low power consumption. Operates with no need for filter. Including 19mm (3/4") and 25mm (1") straight connectors. 4,5A fuse. Interchangeable with Johnson Pump 10-13350-03.

SKU: 03-01-001. Category: Waste Water Pumps.

Weight	<i>0,8 kg/1Lb</i>
---------------	-------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Bilge/grey water</i>
-------------	-------------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Waste Water Diaphragm Pump 22L (5.8 GPM) 24V

Single chamber, self priming, diaphragm pump 24V for grey or bilge water. Shower drain, transfer or pump out. Capacity 22 L/min (5,8 GPM), flexible installation with 360 degree rotational ports. Quiet operation and low power consumption. Operates with no need for filter. Including 19mm (3/4") and 25mm (1") straight connectors. 2,5A fuse. Interchangeable with Johnson Pump 10-13350-04.

SKU: 03-01-002. Category: Waste Water Pumps.

Weight	<i>0,8 kg/1Lb</i>
---------------	-------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Bilge/grey water</i>
-------------	-------------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Waste Water Diaphragm Pump 32L (8.5 GPM) 12V

Single chamber, self priming, heavy duty diaphragm pump 12V for waste water. Black water transfer or pump out. Capacity 32 L/min (8,5 GPM), flexible installation with 360 degree rotational ports. Quiet operation and low power consumption. Operates with no need for filter, equipped with double non-return valves. Self priming up to 2,5 m. Including 38mm (1,5") straight and 90 degree rotational connectors. Amperage 6A. Interchangeable with Johnson Pump 10-13373-03.

SKU: 03-01-003. Category: Waste Water Pumps.

Weight	<i>1 kg/1.5Lb</i>
---------------	-------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Black water</i>
-------------	--------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Waste Water Diaphragm Pump 32L (8.5 GPM) 24V

Single chamber, self priming, heavy duty diaphragm pump 24V for waste water. Black water transfer or pump out. Capacity 32 L/min (8,5 GPM), flexible installation with 360 degree rotational ports. Quiet operation and low power consumption. Operates with no need for filter, equipped with double non-return valves. Self priming up to 2,5 m. Including 38mm (1,5") straight and 90 degree rotational connectors. Amperage 3A. Interchangeable with Johnson Pump 10-13373-04.

SKU: 03-01-004. Category: Waste Water Pumps.

Weight	<i>1 kg/1.5Lb</i>
---------------	-------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Black water</i>
-------------	--------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Waste Water Macerator 43L (11.5 GPM) 12V

Macerator Pump 12V equipped with rotary cutter and impeller to discharge waste water with high capacity. Capacity 43 L/min (11,5 GMP) output at 4 m total head. Self priming up to 1,5 m vertical lift. Brass and stainless steel internal parts and pump body in thermo polymer with a long lasting impeller. Inlet port 38mm (1,5") and outlet 25mm (1"). Amperage 12A. Interchangeable with Jabsco 18590-2092, Johnson Pump 10-24453-04.

SKU: 03-01-005. Category: Waste Water Pumps.

Weight	<i>1,98 kg/4Lb</i>
---------------	--------------------

Dimensions	<i>240/9.4L x 90/3.5H x 130/5W mm/in</i>
-------------------	--

Type	<i>Black water</i>
-------------	--------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Waste Water Macerator 43L (11.5 GPM) 24V

Macerator Pump 24V equipped with rotary cutter and impeller to discharge waste water with high capacity. Capacity 43 L/min (11,5 GMP) output at 4 m total head. Self priming up to 1,5 m vertical lift. Brass and stainless steel internal parts and pump body in thermo polymer with a long lasting impeller. Inlet port 38mm (1,5") and out 25mm (1"). Amperage 7A. Interchangeable with Jabsco 18590-2094, Johnson Pump 10-24453-05.

SKU: 03-01-006. Category: Waste Water Pumps.

Weight	<i>1,98 kg/4Lb</i>
---------------	--------------------

Dimensions	<i>240/9.4L x 90/3.5H x 130/5W mm/in</i>
-------------------	--

Type	<i>Black water</i>
-------------	--------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Compact Waste Water Diaphragm Pump 22L (5.8 GPM) 12V

The most compact single chamber, self priming, diaphragm pump 12V for grey or bilge water. Shower drain, transfer or pump out. Capacity 22 L/min (5,8 GPM), flexible and very compact installation with 360 degree rotational in-line ports. Quiet operation and low power consumption. Operates with no need for filter. Including 19mm (3/4") and 25mm (1") straight connectors. 4,5A fuse.

SKU: 03-01-015. Category: Waste Water Pumps.

Weight	<i>0,8 kg/1 Lb</i>
---------------	--------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Bilge/grey water</i>
-------------	-------------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---



Compact Waste Water Diaphragm Pump 22L (5.8 GPM) 24V

The most compact single chamber, self priming, diaphragm pump 24V for grey or bilge water. Shower drain, transfer or pump out. Capacity 22 L/min (5,8 GPM), flexible and very compact installation with 360 degree rotational in-line ports. Quiet operation and low power consumption. Operates with no need for filter. Including 19mm (3/4") and 25mm (1") straight connectors. 2,5A fuse.

SKU: 03-01-016. Category: Waste Water Pumps.

Weight	<i>0,8 kg/1 Lb</i>
---------------	--------------------

Dimensions	<i>141/5.5L x 105/4H x 140/5.5W mm/in</i>
-------------------	---

Type	<i>Bilge/grey water</i>
-------------	-------------------------

Certification	<i>CE marked 94/25/ECC, ISO8846 Small Craft, Electromagnetic compatibility 89/336/EEC, EN51014 1993/radio disturbance</i>
----------------------	---
